



5m Cable:  
**XO-326IIsA**  
**XO-326IIsA-V**  
(Vibration)



1m Spiral Cable:  
**XO-326IIsB**  
**XO-326IIsB-V**  
(Vibration)



10m Cable:  
**XO-326IIsC**  
**XO-326IIsC-V**  
(Vibration)

**FEATURES**

- Continuously for up to 15,000 hours with 2 × AA alkaline batteries
- Automatic Air Adjustment
- Plug-in sensor installed

**SPECIFICATIONS**

Model	XO-326IIsA XO-326IIsA-V	XO-326IIsB XO-326IIsB-V	XO-326IIsC XO-326IIsC-V
Cable Length	5m	1m (spiral cable)	10m
Target Gas	Oxygen		
Detection Principle	Galvanic cell		
Sampling Method	Diffusion Type		
Detection Range	0 to 25.0 vol%		
(Service Range)	(25.1 to 40.0%)		
Indication Accuracy	Within +/-0.5vol%		
Display Resolution	0.1 vol%		
Alarm Set Value	1st stage: 19.5 vol% 2nd stage: 18.0 vol%		
Response Time	Within 20 seconds		
Alarm Function	Buzzer sounds, Red lamp blinks, LCD display blinks (latching), Vibration (for vibration specifications)		
Power Source	2 × size AA alkaline battery (LR6/ made by PANASONIC)		
Continuous Use	Approx. 15,000 hours		
Explosion-proof Structure	Ex ia II CT3 X (Japan)		
Protection Class	IP20 or equivalent		
Operating Temperature/ Humidity	-10 to 40 degrees C 30 to 85% RH (non condensing)		
Dimensions (mm) (excluding protrusions)	66(W) × 170(H) × 29(D)	66(W) × 120(H) × 29(D)	66(W) × 200(H) × 29(D)
Weight	Approx. 340g	Approx. 265g	Approx. 410g

Conforms to JIS T 8201  
The Ship Equipment Inspection Society of Japan (HK) approved product  
(Designation required)