

Analytical balance Talent TE214S



Standard features.

- Bright all-glass draft shield chamber with smooth-action doors
- Weighing pan and weighing chamber base plate made of stainlesss steel (base plate can be removed)
- Large, high-contrast LCD
- High level of operating convenience thanks to keys with positive click action and 2 tare keys
- Built-in application programs: counting, weighing in %, net-total formulation; averaging; toggling between 2 units
- Bidirectional RS-232C data interface port

- ISO/GLP-compliant logging capability for calibration, adjustment and weighing data in conjunction with the optional YDP03-0CE data printer
- Four digital filter levels for adaptation of the balance to the conditions at the place of use
- Mechanical overload protection
- Dust cover

| Readability | 0.1 mg |
|----------------------|----------------|
| Weighing capacity | 210 g |
| Pan size | Ø 90 mm |
| Response time (avg.) | 3 s |
| Housing (WxDxH) | 200x270x299 mm |
| Reproducibility | <=± 0.1 mg |
| Linearity | <=+ 0.2 mg |

| Key accessories | Order no. |
|--|------------|
| Data printer with date, time and statistics functions | YDP03-0CE |
| Data transfer software SartoConnect with RS-232C standard cable (1.5 m); | YSC01L |
| Test and calibration weight: 200 g, accuracy class E2 | YCW5228-00 |
| External rechargeable battery pack | YRB08Z |
| In-use dust cover for the display and control unit | 6960TE01 |



Data printer



SartoConnect